



# XTS TRUCKS 5W30

## DESCRIPTION

Low viscosity fully synthetic oil made from last generation performance additives and formulated for turbo-charged (or not) heavy diesel engines (trucks, busses and delivery vans) to reduce friction, eliminate sludge and optimize fuel consumption. Offers a good general protection of the engine.

## APPLICATION

**Bardahl XTS Trucks 5w30** has an excellent fluidity at low temperature. It also provides excellent dispersion and detergency performance. Suitable for Euro 3, 4 and 5 engines in combination with low sulfur diesel. Following the official instructions, the XTS Trucks 5w30 is authorized for extended emptying intervals.

## SPECIFICATIONS

This product offers the following performance level:

ACEA	E4/E7
API	CI-4
MB	228.5
RENAULT VI	RXD/ RLD-2
DAF	HP1/ HP2
DEUTZ	DQC IV-10
VOLVO	VDS-3
MACK	EO-N/ EO-MPLUS
MAN	M3377/ M3277
MTU	Type3
CAT	ECF-2
CUMMINS	20076/ 20078
GLOBAL	DHD-1
JASO	DH-1
SCANIA	LDF





## PROPERTIES

- ✓ Contains powerful detergency additives to avoid the formation of deposits,
- ✓ Offers excellent dispersion properties,
- ✓ Provides a high resistance against corrosion and oxidation,
- ✓ Offers a stable viscosity and a high viscosity index,
- ✓ Avoids fuel overconsumption,
- ✓ Contains anti-foam and anti-wear additives.

## TECHNICAL DATA

Densité à 15°C	Kg/l	0,855
Viscosité -35°C	mPa.s	6420
Viscosité 40°C	mm2/s	71,6
Viscosité 100°C	mm2/s	12,17
Indice de Viscosité		168
Point d'éclair COC, °C	°C	224
Point d'écoulement, °C	°C	-39
Alcalinité TBN	mgKOH/g	12,2
Cendres Sulfatées	%	1,35

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

## RECOMMENDATIONS

**Handling :** any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

**Storage :** it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

## REFERENCES & AVAILABILITIES

36208	20 L
36204	60 L
36207	205 L



**NOTHING WILL STOP YOU**

SADAPS BARDAHL ADDITIVES & LUBRICANTS  
Rue du Mont des Carliers, 3 ZI TOURNAI Ouest, 2  
T: (+32) (0) 69 59 03 60

[www.bardahl.fr](http://www.bardahl.fr)  
[www.bardahlois.com](http://www.bardahlois.com)