



XTC C60

DESCRIPTION

XTC C60 Synthetic Special Oil is a Premium Performance lubricant for aspirated or supercharged engines of gasoline vehicles and for diesel and turbodiesel engines with direct injection.

The use of precious bases and special high stability polymers permits to achieve extraordinary performances in terms of resistance to thermal deterioration and strength of the lubricating oil veil even under the most severe conditions of working, thus permitting to extend the interval of oil changes up to the maximum limit indicated by the manufacturer.

Its excellent viscosimetrics permit an immediate lubrication at setting in motion and, while in motion, permit to contain the wear due to the lowering of viscosity at high temperatures, thanks to the high HTHS value.

Thanks to the Bardahl technology and the effective Polar Plus formula with Fullerene, XTC C60 Synthetic Special Oil permits a notable reduction of friction to the benefit of the performance of the propeller, a saving of fuel and the protection of all mechanic parts. It also helps keeping the engine clean and so extends its life.

SPECIFICATIONS

This product offers the following performance level:

5w40	
ACEA	A3/B4
API	SN
BMW	LL-01
MB	226.5/229.3/229.5
VW	502.00/505.00
PORSCHE	A40



NOTHING WILL STOP YOU

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers, 3 ZI TOURNAI Ouest, 2
T: (+32) (0) 69 59 03 60

www.bardahl.fr
www.bardahlois.com



RENAULT	RN0700/0710
PSA	B71 2296
10w40	
ACEA	A3/B4
API	SN/CF
MB	229.5
VW	502.00/505.00
RENAULT	RN0700/0710

PROPERTIES

- ✓ Better control of wear
- ✓ Longer life and cleanliness of all parts of the engine
- ✓ Easy start and immediate lubrication at low temperature
- ✓ 100% synthetic formula

TECHNICAL DATA

	5w40	10w40
Viscosity at 40°C	76	88
Viscosity at 100°C	13,4	14,4
Viscosity Index	0,852	0,852
Viscosity at 40°C	181	170
Flash point	200	201,5
Pour Point	-48	-48
T.B.N.	10,5	10,5

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.





RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

5w40	
334040	24x1L
334053	60L
334054	200L
10w40	
326040	24x1L
326053	60L
326054	200L

