



# XTG CVT

## DESCRIPTION

Very high-performance fluid formulated for Continuously Variable Transmissions (CVTs). Suitable for CVT chain and CVT belt.

## APPLICATION

**Bardahl XTG CVT** allows limiting fuel overconsumption on vehicles equipped with a CVT transmission.

## SPECIFICATIONS

This product offers the following performance level:

BMW - Mini Cooper	EZL799 / EZL799A
MERCEDES	236.20
VW	G 052 180/ G 052 516
NISSAN	NS-1/ NS-2/ NS-3
HONDA	HMMF (without starting clutch)/ HCF2
MITSUBISHI	SPIII (only in CVT)/ CVTF-J1/J4/J4+
SUBARU	ECVT/iCVT/iCVT FG/NS-2 / Lineartronic High Torque (HT) CVTF / Lineartronic chain CVTF/CVTF II
DAIHATSU	AMIX CVTF DC/DFE / DFC
SUZUKI	CVTF TC/ 3320/ NS-2/ Green 1/ Green 2/ Green 1V
HUYNDAI	CVT-J1/ SPIII (CVT Model)
KIA	CVT-J1/ SPIII (CVT Model)
CHRYSLER JEEP DODGE	NS-2 / Mopar CVTF+4
TOYOTA	CVTF TC/FE
FORD	WSS-M2C928-A
MOPAR	CVTF+4
MAZDA	JWS 3320
GM	DEX-CVT

## PROPERTIES

- ✓ Has a very low pour point,
- ✓ Has a very high and stable viscosity index,
- ✓ Performs well against friction,
- ✓ Provides antivibration performance,
- ✓ Extends the fuel drain intervals,
- ✓ Provides a good resistance against oxidation and corrosion,
- ✓ Offers anti-wear, anti-foam, and anti-shudder properties.





## TECHNICAL DATA

Density at 20°C	Kg/l	0,845
Viscosity at 40°C	mm <sup>2</sup> /s	35,4
Viscosity at 100°C	mm <sup>2</sup> /s	7,3
Viscosity Index		177
Flash point COC, °C	°C	214
Pour point, °C	°C	-48
TBN alcalinity	mgKOH/g	3,6

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

## RECOMMENDATIONS

**Handling :** any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

**Storage :** it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

## REFERENCES & AVAILABILITIES

36501	12 x 1 L
36508	20 L

