



# ATF DIII

## DESCRIPTION

Transmission fluid for automatic transmissions, power steering systems, torque converters and other applications requiring an ATF DIII fluid.

## APPLICATION

**BARDAHL ATF DIII** is particularly suitable for the transmissions (built after 1997) of passenger cars, delivery vans and trucks.

## SPECIFICATIONS

This product offers the following performance level:

GM	Dexron IID/IIE/IIIF/IIIG/IIIH
ZF	TE-ML 02F/03D/04D/09A/09B/11A/11B/14A/17C
FORD	Mercon/M2C138-CJ/166-H
VOLVO	97341
MAN	339V1/ 339Z1
CAT	TO-2
ALLISON	C4 / TES-389
MB	236.1/236.5/236.6/236.7/236.9
VOITH	55.6335 (G607)

## PROPERTIES

- ✓ Has a low pour point,
- ✓ High viscosity index,
- ✓ Offers a good stability,
- ✓ Is highly resistant against corrosion and oxidation.





## TECHNICAL DATA

Densité à 20°C	Kg/l	0,851
Viscosité 40°C	mm <sup>2</sup> /s	37,7
Viscosité 100°C	mm <sup>2</sup> /s	7,6
Indice de Viscosité		175
Point d'éclair COC, °C	°C	210
Point d'écoulement, °C	°C	-51

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

## RECOMMENDATIONS

**Handling :** any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

**Storage :** it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

## REFERENCES & AVAILABILITIES

36281	12 x 1 L
36283	3 X 5 L
36288	20 L
36284	60 L
36237	205 L