



# XTS-M 2T LV

## DESCRIPTION

BARDAHL XTC-M 2T LV is a new generation 2-stroke fully synthetic ester-based oil developed to ensure the best engine cleanliness.

## SPECIFICATIONS

This product offers the following performance level:

API	TC
JASO	FD

## PROPERTIES

- ✓ Suitable for oil injector systems or premix. Mixing ratio: from 2% to 4%.
- ✓ BARDAHL has selected the best hydrotreated synthetic bases to ensure more stability, better performance and energy-saving.
- ✓ Low friction coefficient, and performance meeting the expectations of the most demanding motorcyclists.
- ✓ The BARDAHL performance additives used in this formula will guarantee an excellent anti-wear action.
- ✓ Shear resistance to protect moving parts and ensure engine and gearbox lifespan.
- ✓ Anti-corrosion, anti-foam and anti-smoke properties.
- ✓ Good dispersion and detergency properties.



## TECHNICAL DATA

<b>Colour</b>		Blue
<b>Density at 15°C – kg/l</b>	ASTM D1298	0,860 (20°C)
<b>Viscosity at 40°C – mm<sup>2</sup>/s</b>	ASTM D445	64,8
<b>Viscosity at 100°C – mm<sup>2</sup>/s</b>	ASTM D445	9,58
<b>Viscosity Index</b>	ASTM D2270	135
<b>Pour point - °C</b>	ASTM D97	-30
<b>TBN – mgKOH/g</b>	ASTM D2896	1,54
<b>Flash point - °C</b>	ASTM D92	>140

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

## RECOMMENDATIONS

**Handling :** any safety information related to the handling and use of this product are gathered in the Safety Data Sheet. Always check the manufacturer manual before use. Miscible with other 2-stroke motorbike oils.

**Storage :** it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

## REFERENCES & AVAILABILITIES

35781	12x1L
-------	-------