



Technos XFS C2/C3

DESCRIPTION

Technos XFS C2-C3 is a Premium mid SAPS Technology lubricant for gasoline and diesel engines of the last generation equipped with exhaust gas after-treatment systems that require a SAE 5W-30 lubricant of ACEA C2 and ACEA C3 levels.

The precious synthetic bases and the special high shear stability polymers employed in the formula give Technos XFS extraordinary properties of resistance against thermal deterioration due to oxidation, of strength of the lubricating oil veil and of fluidity at low temperatures.

Bardahl XFS technology - eXtra Fluid Shield - gives the lubricant an additional reserve of performance in terms of reduction of the friction coefficient, protection against wear and deposit control, while ensuring the prolonged efficiency of the exhaust aftertreatment systems and the increase of the fuel economy.

XFS technology Low Ash supplementary additive, developed specifically for the latest generation engines, offers maximum compatibility with exhaust after-treatment systems. It improves oxidation resistance, inhibits the formation of deposits, contains anti-wear, anti-scuffing and anti-friction agents.

XFS, eXtra Fluid Shield, intervenes as one extra shield, to protect all lubricated components and to maintain engine performance over time.

PROPERTIES

- Maximises engine performance.
- Greater longevity and cleanliness of all engine parts.
- Safeguard the functionality of particle filters and catalytic converters.
- Easy starting and immediate lubrication at low temperature.
- Maximum extension of oil change intervals.
- 100% synthetic formula.





SPECIFICATIONS

ACEA C2-C3 / API SN-CF / MB 229.52-229.51-229.31-226.5 / BMW LL-04 (N20 Performance) / GM Dexos 2 / Renault RN0700-RN0710

TECHNICAL DATA

	5w30
Viscosity at 40°C	64.7
Viscosity at 100°C	11.8
Viscosity at 15°C	0.852
Viscosity Index	178
Flash point	208
Pour Point	-45
T.B.N.	8.2

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

5w30	
342040	24x1L
342053	60L
342054	200L

