



XTS-M 10w50



DESCRIPTION

BARDAHL XTS-M 10w50 is a new generation fully synthetic oil developed to ensure the best engine cleanliness. It has been formulated for high performance 4-stroke motorbike engines with wet or dry clutch. Up to Euro 5 standard, with post-treatment system.

SPECIFICATIONS

This product offers the following performance level:

API	SN / SM / SL / SJ / SH / SG
JASO	MA2

PROPERTIES

- ✓ BARDAHL has selected the best hydrotreated synthetic bases and the best esters to ensure more stability, better performance and energy-saving.
- ✓ Low friction coefficient, and performance meeting the expectations of the most demanding motorcyclists.
- ✓ The BARDAHL performance additives used in this formula will guarantee an excellent anti-wear action.
- ✓ Shear resistance to protect moving parts and ensure engine and gearbox lifespan.
- ✓ Very good friction characteristics.
- ✓ Anti-corrosion and anti-foam properties.
- ✓ Good dispersion and detergency properties.



TECHNICAL DATA

Colour		Amber
Density at 20°C – kg/l	ASTM D1298	0,862 (20°C)
Viscosity at 40°C – mm ² /s	ASTM D445	126,52
Viscosity at 100°C – mm ² /s	ASTM D445	17,73
Viscosity Index	ASTM D2270	163
MRV Viscosity at -30°C – mPa.s	ASTM D4684	<60000
Pour point - °C	ASTM D97	-30
CCS -25°C – mPa.s	ASTM D5293	6654
TBN – mgKOH/g	ASTM D2896	6,6
Flash point - °C	ASTM D92	>210

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet. Always check the manufacturer manual before use. Miscible in other synthetic 4T motorbike oils.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

35751	12x1L
-------	-------